

Ecostick® 307

Ecostick 307 is designed to provide high yield and fast drying times. It is ideal for use in a wide variety of applications, particularly with foams, fibers, and fabrics.

Applicable Surfaces :



Foams



Fabric



Leather



Non wovens

Key Properties :

High Yield | Instant Bond | Fast Processing | Fast Drying | Soft Bond Line | Solvent Free

Application Method :



Roll Coater



Automatic Spray



Manual Spray

Ecostick® 409

Ecostick 409 is designed to provide fast drying times allow for quick assembly and production, increasing overall efficiency.

Applicable Surfaces :



Foams



Fabric



Leather



Non wovens

Key Properties :

High Yield | Instant Bond | Fast Processing | Fast Drying | Soft Bond Line | Solvent Free

Application Method :



Roll Coater



Automatic Spray



Manual Spray

Ecostick® 490

Ecostick 490 is a reliable & versatile adhesive that can be used in many different applications with high-yielding & instant tack properties.

Applicable Surfaces :



Foams



Fabric



Leather



Non wovens

Key Properties :

High Yield | Instant Bond | Fast Processing | Fast Drying | Soft Bond Line | Solvent Free

Application Method :



Roll Coater



Automatic Spray



Manual Spray

Ecostick® 504

Ecostick 490 adhesives is known for their high tack and strong bonding properties, making them ideal for use in a range of applications.

Applicable Surfaces :



Foams



Fabric



Leather



Non wovens



Rubber



Cardboard

Key Properties :

High Yield | Instant Bond | Fast Processing | Fast Drying | Soft Bond Line | Solvent Free

Application Method :



Roll Coater



Automatic Spray




Manual Spray

Ecostick® 715

Ecostick 715 is known for its super instant tack, high yield, high temperature resistance, & fast drying. It is an adhesive, and does not require any mixing before use, and it can be applied directly to the substrate.

Applicable Surfaces :



Key Properties :

High Yield | Instant Bond | Fast Processing | Fast Drying | High temperature resistance | Soft bond line | Solvent free

Application Method :



Ecostick® 916

Ecostick 916 is a hybrid polyurethane adhesive which is used for wide variety of applications. It is perfect for bonding non-porous surfaces.

Applicable Surfaces :



Key Properties :

Bonds to many materials | High yield & Instant bond | Fast processing & drying | One-sided application | High temperature resistance | Solvent free | Excellent bonding to non-porous materials


Application Method :



Ecostick® 2005

Ecostick 2005 is an acrylic pressure sensitive adhesive. It is ideal for flexible applications.

Applicable Surfaces :



Key Properties :

Bonds to many materials | High yield & Instant bond | Fast processing & drying | One-sided application | High temperature resistance | Soft bond line & Solvent free


Application Method :



Ecostick® Speed-Cataly

It speeds up drying time of adhesive and helps in getting strong initial bonding.

Applicable Surfaces :



Key Properties :

Consistency | Versatile | Mold + Mildew Inhibitors | Performance | Solvent free

Application Method :

